

Expert Power Control 8001-1

new



5

Switched PDU with 5 load outputs and power monitoring per port for top-hat rail



Expert Power Control 8001-1:
Compact IP power distribution unit for DIN rail

Features

- 5 load outputs individually switchable directly on the device, via HTTPS, SNMP or command line tool
- Status and Power-up delay (0...9999 seconds) adjustable individually for each output after power blackout
- Simultaneous power-up of multiple outputs prevented by latency time of 1 second
- Programmable turn-on/turn-off sequence
- Switching of outputs dependent on sensor threshold or inputs possible
- 2 energy counters per load output, one counter counts permanently, the other counter is resettable (outlet-metered)
- Metering of energy, current, power factor, phase angle, frequency, voltage and active/apparent/reactive power
- 5-channel watchdog to monitor connected consumers (ICMP/TCP)
- Interface for plug-n-play sensors for environmental monitoring (temperature, humidity and air pressure)
- Messages by e-mail, Syslog and SNMP traps, Telnet, SSH and MQTT depending on threshold values of sensor metering and signal input as well
- LED display for total current, IP address, sensor data and error reports
- Bicoloured LEDs display status information of inputs/outputs
- Comfortable configuration by web browser, Windows or Linux tool
- Firmware update via Ethernet during operation
- IPv6-ready
- HTTP/HTTPS, e-mail (SSL, STARTTLS), DHCP, Syslog

- SNMPv1, v2c, v3 (Get/Traps)
- TLS 1.1, 1.2, 1.3
- Radius, Modbus TCP and MQTT 3.1.1 support
- Configuration and control via SSH and Telnet
- IP Access Control List
- Android and iOS app *Gude Control* allows access from anywhere
- Compact housing for easy mounting on top-hat rail
- Low internal power consumption
- Developed and manufactured in Germany

Electrical Connections

- Operation with 230 V AC (terminal clamp)
- 5 switchable outputs (terminal clamp)
- Ethernet connector RJ45 (10/100 Mbit/s)
- Sensor connector RJ45 for plug-n-play sensors

Technical Details

- LxHxD: 143 x 65 x 90 mm
- Weight: ca. 400 g
- Operating temperature: 0-45 °C
- Storage temperature: -20 - 70 °C
- Relative humidity: 0 - 95 % (non-condensing environment)

<input checked="" type="checkbox"/> IPv6	<input checked="" type="checkbox"/> SSH
<input checked="" type="checkbox"/> HTTPS	<input checked="" type="checkbox"/> SNMPv3
<input checked="" type="checkbox"/> SSL	<input checked="" type="checkbox"/> Modbus TCP
<input checked="" type="checkbox"/> Telnet	<input checked="" type="checkbox"/> MQTT

Order code	Product	Feature	Power supply
8001-1	Expert Power Control 8001-1	5 switchable outputs, output-metered, 1 sensor port	230 V AC
7101	Temperature Sensor 7101	Cable sensor with splash-proof sensor head (IP64), RJ45 connector, -20°C to +80°C, cable ca. 2.3 m	
7104 *	Temperature Sensor 7104	Cable sensor, RJ45 connector, -20°C to +80°C, cable ca. 2.3 m	
7105 *	Temp., Humidity Sensor 7105	Cable sensor, RJ45 connector, -20°C to +80°C, 0-90% humidity, cable ca. 2.3 m	
7106 *	Temp., Humidity, Air pressure Sensor 7106	Cable sensor, RJ45 connector, 20°C to +80°C, 0-90% humidity, 300-1100 hPa, cable ca. 2.3 m	

* Sensors also available with calibrated temperature range: 7104-2, 7105-2, 7106-2